



**vehicles for professionals**



**LTV X 4x4**  
LIGHT TACTICAL VEHICLE

**BUILT BY PROFESSIONALS  
FOR PROFESSIONALS**



Dimensions & Weight	
<b>Length</b> up to	6000 mm
<b>Width</b>	2150 mm
<b>Vehicle Height (roof line)</b> up to	2450 mm
<b>Wheelbase</b>	Standard Long
<b>Gross Vehicle Weight</b> up to	7000 kg
<b>Payload on chassis</b> up to	3400 kg

Performance	
<b>Speed</b> up to	120 km/h
<b>Power to Weight Ratio</b>	33 HP/ton
<b>Acceleration</b> 0 - 60 km/h	9.5 sec
<b>Turning Radius</b>	7.8 - 9.2 m
<b>Gradeability</b> up to	60%
<b>Side Slope</b> up to	40%
<b>Approach Angle</b> up to	80°
<b>Departure Angle</b> up to	60°
<b>Ground Clearance</b>	410 mm
<b>Fording Depth</b>	760 mm


Vehicle Engine	
Diesel engine with exhaust Turbo charger, Intercooler and Common rail direct injection.	
Water cooled, -32 to +49C°	
<b>Engine Power</b> up to	230 HP
<b>Torque</b> up to	510 Nm
<b>Fuel Tank</b>	80 l

Drivetrain	
<b>Transmission</b>	Fully automatic with torque converter
<b>Transfer case</b>	High-low range
<b>Axles</b>	Double wishbone independent suspension portal axles at front & rear with heavy duty coil spring and hydraulic shock absorbers Rear Axle Automatic Diff. Locking Front Axle Diff. Lock (optional)
<b>Steering</b>	Left hand or Right hand Power Steering
<b>Brakes</b>	Hydraulic Disc Brakes, ABS, EBD
<b>Electrical</b>	24V system, 2 batteries 12V 100Ah each 24V charging socket, BO & IR-Lights
<b>Climate control</b>	Heating & Air Conditioning
<b>Tire Inflation System</b>	STIS or CTIS (optional)

Special Features
Electromagnetic Compatibility acc. to MIL-STD-461 & MIL-STD464
Vehicle Family with Bodies for:
<ul style="list-style-type: none"> <li>• Multipurpose Troop &amp; Cargo,</li> <li>• Special Operations Vehicle,</li> <li>• Single Cab,</li> <li>• Double Cab,</li> <li>• Ambulance/Communications Shelter, etc.</li> </ul>

Options
<ul style="list-style-type: none"> <li>• Flywheel Generator with Power Management Module</li> <li>• Recovery Winch with front &amp; rear attachment</li> <li>• Airlift outside load attachment</li> <li>• Runflat &amp; Beadlock System</li> <li>• Roof Hatch, foldable Windshield</li> <li>• Integration of Customer Navigation, Radio, Camera Systems, etc.</li> </ul>

**STEYR Trucks**  
Sales & Services International GmbH  
Hohe-Linde-Strasse 1  
A-4595 Waldneukirchen, Austria  
office@sti-steyr.com



**Steyr Trucks International FZE**  
RAKEZ Al Hulaila Industrial Zone  
Ras Al Khaimah  
United Arab Emirates  
office@sti-defense.com