

vehicles for professionals



BUILT BY PROFESSIONALS FOR PROFESSIONALS



Dimensions & Weight	
Length up to	6000 mm
Width	2200 mm
Vehicle Height (roof line) up to	2050 mm
Wheelbase	3290 mm
Gross Vehicle Weight up to	7000 kg
Payload up to	3000 kg

Performance	
Speed up to	120 km/h
Range up to	500 km
Acceleration 0 - 60 km/h	9.5 sec
Turning Radius	7.8 - 9.2 m
Gradeability up to	60%
Side Slope up to	40%
Ground Clearance	400 mm

Protection up to	
Kinetic	STANAG 4569 Level 2
Mine Blast	STANAG 4569 Level 2a
IED (side blast)	20 kg TNT

Vehicle Engine	
Diesel engine with exhaust Turbo charger, Intercooler and Common rail direct injection.	
Water cooled, -32 to +49C°	
Engine Power up to	230 HP
Torque up to	510 Nm
Fuel Tank	80 I

Drivetrain	
Transmission	Fully automatic with torque converter
Transfer case	High-low range
Axles	Double wishbone independent suspension portal axles at front & rear with heavy duty coil spring and hydraulic shock absorbers
	Rear Axle Automatic Diff. Locking Front Axle Diff. Lock (optional)
Steering	Left hand or Right hand Power Steering
Brakes	Full Hydraulic Disc Brakes, ABS
Electrical	24V system, 2 batteries 12V 100Ah
Climate control	Heating & Air Conditioning
Tire Inflation System	CTIS (optional)













Fast Evacuation
Ambulance

APC

Anti Riot Police

Side Loading Doors

Forward Observer Vehicle Radar & Surveillance Vehicle

STEYR Trucks
Sales and Services International GmbH
Hohe-Linde-Strasse 1
A- 4595 Waldneukirchen
Austria
office@sti-steyr.com

STEYR Trucks
International FZE
Al Hulaila Industrial Zone
Ras Al Khaimah
United Arab Emirates
www.sti-defense.com